

**SUPPORTING MULTIPLE DATA CHANNELS IN A CABLE
MODEM TERMINATION SYSTEM**

Technical Field

5 The present invention relates generally to telecommunications systems, and more specifically to supporting multiple data channels in a cable modem termination system.

Background

10 Telecommunications networks provide a mechanism for exchanging data, e.g., voice, video, and other data, between terminal equipment at various locations. One type of telecommunications transmission system is the conventional broadband hybrid fiber/coax (HFC) cable network. Cable networks were originally developed to deliver video and audio content to subscribers over a network of coaxial cables.

15 Over the years, cable networks have evolved. Many cable networks have been updated through the use of fiber optic cable, hence the term hybrid fiber/coax (HFC) networks. In an HFC network, a head end typically is coupled to a plurality of optical distribution nodes through fiber optic cables. The optical distribution nodes are also coupled to coaxial cables that connect terminal equipment with the
20 network. At the optical distribution node, signals are converted between optical and electrical formats for transmission on the fiber optic cables and the coaxial cables.

 Originally, the HFC networks provided downstream (i.e., from the head end to the terminal equipment) transmission to terminal equipment from audio, video and data sources. Recently, service providers have modified their systems to allow
25 signals to be transmitted upstream, from the terminal equipment to the head end. This allows services such as telephony, video on demand, pay per view, Internet access and other data services to be provided over the existing coaxial and fiber optic cables, using, for example cable modems, set top boxes and the like.

 One type of cable modem uses a standard referred to as Data Over Cable
30 Service Interface Specification (DOCSIS). This specification allows equipment developed by different manufacturers to communicate with one another over the

network. The cable modems are connected to the cable network at the subscriber location. The cable modems communicate over the network with a device at the head end referred to as a Cable Modem Termination System (CMTS). A typical CMTS provides a card or chassis with a downstream data port and a number of upstream data ports. Each CMTS allows a service provider to serve a selected number of customers, e.g., one card may be sufficient for 1000 homes on the network.

Demand for data services continues to increase with popularity of the Internet and the like. Thus, service providers continue to increase the capacity of their systems to meet this rising demand. To increase the capacity of their systems, service providers typically install additional CMTS cards and chassis at great expense.

What is needed is a mechanism for increasing the port density of a CMTS within the confines of existing chassis and card sizes.

Summary

Embodiments of the present invention overcome problems with existing cable modem termination systems (CMTS). Embodiments of a CMTS circuit are provided. Each embodiment provides an increase in the number of subscribers supported by a single CMTS circuit while occupying the same physical space as existing CMTS cards or chassis. For example, the CMTS circuit uses the same physical interface as existing CMTS cards or chassis. In one embodiment, this is accomplished by using a plurality of media access control (MAC) circuits. Each MAC circuit supports a single downstream channel. The downstream channels are combined and upconverted using a single upconverter. Advantageously, the reuse of the upconverter allows sufficient savings in space in the CMTS circuit that multiple downstream channels can be supported in a single CMTS card or chassis.

In one embodiment, a circuit for a cable modem termination system is provided. The circuit includes a backplane interface and a packet processing engine coupled to the backplane interface. The circuit further includes a plurality of media access control (MAC) circuits, each media access control circuit coupled to the

packet processing engine, each MAC circuit supporting one of N contiguous downstream channels with a single upconverter and each MAC circuit also supporting a plurality of upstream channels.

Other embodiments are described and claimed.

5

Brief Description of the Drawings

Figure 1A is a block diagram of one embodiment of a circuit for a cable modem termination system that supports multiple downstream channels according to the teachings of the present invention.

Figure 1B is a block diagram of another embodiment of a circuit for a cable modem termination system that supports multiple downstream channels according to the teachings of the present invention.

Figure 2 is a graph that illustrates one embodiment a spectrum allocation for downstream data channels for a cable modem termination system according to the teachings of the present invention.

Figure 3 is a graph that illustrates one embodiment of a spectrum allocation for upstream data channels for a cable modem termination system according to the teachings of the present invention.

Figure 4 is a block diagram of one embodiment of a system including a cable modem termination system that supports multiple downstream channels according to the teachings of the present invention.

Detailed Description

In the following detailed description of the embodiments, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration specific embodiments in which the invention may be practiced. It is to be understood that other embodiments may be utilized and structural changes may be made without departing from the scope of the present invention.

30

Figure 1A is a block diagram of one embodiment of a circuit, indicated generally at 10, for a cable modem termination system that supports multiple downstream channels according to the teachings of the present invention. Circuit 10 advantageously increases the port density without increasing the size of the card or chassis compared to existing systems by including a plurality of media access control (MAC) circuits 18-1, . . . , 18-N on the same card or chassis. Each of the MAC circuits 18-1, . . . , 18-N supports a separate downstream channel and a separate plurality of upstream channels. In other words, each MAC circuit 18-1, . . . , 18-N supports a separate MAC domain. The added channels allow circuit 10 to provide a higher number of homes passed compared to existing systems. Further, all of MAC circuits 18-1, . . . , 18-N share the same downstream port 24 and the same upstream ports 26-1, . . . , 26-K. Thus, circuit 10 can be used in the same physical space as existing cards or chassis, thereby increasing the port density without requiring a complete modification of the physical structure of existing systems.

Circuit 10 interfaces with a data network. Circuit 10 includes backplane interface 14 which provides a connection through network interface 12 to the data network for circuit 10. Further, circuit 10 includes packet processing engine 16. In one embodiment, packet processing engine 16 is implemented with one or more processors that are programmed to process data packets for the multiple MAC domains of circuit 10.

Circuit 10 also includes MAC circuits 18-1, . . . , 18-N. These MAC circuits 18-1, . . . , 18-N process packets according to the data over cable service interface specification (DOCSIS) standard. Each MAC circuit 18-1, . . . , 18-N operates separately and independently to process packets in a single downstream channel and a plurality of upstream channels. Thus, by increasing the number of MAC circuits, the capacity of the circuit is increased without the need to change the physical interface of cards or chassis incorporating the circuit.

Circuit 10 includes a downstream data or signal path for carrying signals downstream to cable modems over a plurality of downstream data channels. In the downstream direction, MAC circuits 18-1, . . . , 18-N provide data to downstream channels 20. Downstream channels 20 present modulated data at intermediate

frequencies (IF-1, ..., IF-N) that are offset from one another by the channel spacing. The IF signals are provided to upconverter 22. Upconverter 22 provides the upconverted and amplified output to downstream port 24 for transmission.

An example of the output at downstream port 24 is provided in graph 200 of Figure 2. As shown, N contiguous channels in frequency bands 202-1, ..., 202-N of Y MHz bandwidth, respectively, are provided for the N MAC domains. In one embodiment, each channel has a 6 MHz bandwidth. Alternative channel bandwidths are possible. Advantageously, contiguous frequency bands 202-1, ..., 202-N are used such that a single upconverter 22 can be used to prepare the signals of downstream channels 20 for transmission. The use of a single upconverter greatly reduces the expense and space requirements for supporting the multiple MAC domains on circuit 10 by leveraging common circuitry for a number of MAC circuits. Upconverter 22, in one embodiment, is programmable and thus able to produce an output with an appropriate bandwidth to support the number of downstream channels. In one embodiment, upconverter 22 is programmed to place the contiguous downstream channels at any appropriate frequency band within the range of 90 to 870 MHz.

Circuit 10 also receives signals from cable modems in an upstream direction. In the upstream direction, data is received from cable modems at upstream ports 26-1, ..., 26-K. Each of the upstream ports 26-1, ..., 26-K receives data on a plurality of upstream channels. For example, in one embodiment, each port 26-1, ..., 26-K receives N channels of data. Thus, circuit 10 is designed to provide one of the N channels from each port 26-1, ..., 26-K to a corresponding one of MAC circuits 18-1, ..., 18-N. Advantageously, receiving a plurality of channels at each of the upstream ports allows circuit 10 to increase the capacity of a CMTS using a conventional card or chassis size.

Circuit 10 includes upstream channels 28. In one embodiment, upstream channels 28 provides K upstream channels per MAC with each of the upstream channels for a MAC being received at one of upstream ports 26-1, ..., 26-K. Thus, each MAC circuit processes one downstream channel and K upstream channels. Circuit 10 processes N downstream channels and K*N upstream channels.

In Figure 3, graph 300 illustrates an example of an upstream frequency spectrum for one optical node (see Figure 4) serviced by circuit 10. In this example, upstream channels from a selected optical node are located in the 5-42 MHz frequency range. Each channel for the optical node, e.g., channels 302-1, . . . , 302-K, has a separate and distinct frequency band with one band per port of circuit 10. The frequency allocation for the upstream channels of the other optical nodes serviced by circuit 10 are laid out to allow each node to provide a non-interfering upstream channel to each port of circuit 10. Further, in one embodiment, the frequency bands for the various channels of upstream ports 26-1, . . . , 26-K are not contiguous. Further, it is understood that in other embodiments, the upstream channels are located in other appropriate frequency bands, e.g., 5-65 MHz.

ans. a27 Figure 1B is a block diagram of one embodiment of a circuit, indicated generally at 100, for a cable modem termination system that supports multiple downstream channels according to the teachings of the present invention. Circuit 100 advantageously increases the port density without increasing the size of the card or chassis compared to existing systems by including a plurality of media access control (MAC) circuits 106-1, . . . , 106-N on the same card or chassis. Each of the MAC circuits 106-1, . . . , 106-N supports a separate downstream channel and a separate plurality of upstream channels. In other words, each MAC circuit 106-1, . . . , 106-N supports a separate MAC domain. The added channels allow circuit 100 to provide a higher number of homes passed compared to existing systems. Further, all of MAC circuits 106-1, . . . , 106-N share the same downstream port 114 and the same upstream ports 116-1, . . . , 116-K. Thus, circuit 100 can be used in the same physical space as existing cards or chassis, thereby increasing the port density without requiring a complete modification of the physical structure of existing systems.

Circuit 100 interfaces with a data network. Circuit 100 includes backplane interface 102 which provides a connection through network interface 101 to the data network for circuit 100. Further, circuit 100 includes packet processing engine 104. In one embodiment, packet processing engine 104 is implemented with one or more

processors that are programmed to process data packets for the multiple MAC domains of circuit 100.

Circuit 100 also includes MAC circuits 106-1, . . . , 106-N. These MAC circuits 106-1, . . . , 106-N process packets according to the data over cable service interface specification (DOCSIS) standard. Each MAC circuit 106-1, . . . , 106-N operates separately and independently to process packets in a single downstream channel and a plurality of upstream channels. Thus, by increasing the number of MAC circuits, the capacity of the circuit is increased without the need to change the physical interface of cards or chassis incorporating the circuit.

Circuit 100 includes a downstream data or signal path for carrying signals downstream to cable modems over a plurality of downstream data channels. In the downstream direction, MAC circuits 106-1, . . . , 106-N provide data to downstream modulators 108-1, . . . , 108-N, respectively. Modulators 108-1, . . . , 108-N modulate the data to an intermediate frequency (IF-1, . . . , IF-N) that are offset from one another by the channel spacing. The IF outputs of modulators 108-1, . . . , 108-N are summed in combiner 110 and provided to upconverter 112. Upconverter 112 provides the upconverted and amplified output to downstream port 114 for transmission.

An example of the output at downstream port 114 is provided in graph 200 of Figure 2. As shown, each downstream modulator 108-1, . . . , 108-N is responsible for one of N contiguous channels in frequency bands 202-1, . . . , 202-N of Y MHz bandwidth, respectively. In one embodiment, each modulator 108-1, . . . , 108-N uses a 6 MHz output channel. Alternative channel bandwidths are possible.

Advantageously, contiguous frequency bands 202-1, . . . , 202-N are used such that a single upconverter 112 can be used to prepare the signals from modulators 108-1, . . . , 108-N for transmission. The use of a single upconverter greatly reduces the expense and space requirements for supporting the multiple MAC domains on circuit 100 by leveraging common circuitry for a number of MAC circuits. Upconverter 114, in one embodiment, is programmable and thus able to produce an output with an appropriate bandwidth to support the number of downstream channels. In one

embodiment, upconverter 112 is programmed to place the contiguous downstream channels at any appropriate frequency band within the range of 90 to 870 MHz.

Circuit 100 also receives signals from cable modems in an upstream direction. In the upstream direction, data is received from cable modems at upstream ports 116-1, . . . , 116-K. Each of the upstream ports 116-1, . . . , 116-K receives data on a plurality of upstream channels. For example, in one embodiment, each port 116-1, . . . , 116-K receives N channels of data. Thus, circuit 100 is designed to provide one of the N channels from each port 116-1, . . . , 116-K to a corresponding one of MAC circuits 106-1, . . . , 106-N. Advantageously, receiving a plurality of channels at each of the upstream ports allows circuit 100 to increase the capacity of a CMTS using a conventional card or chassis size.

Splitters 118-1, . . . , 118-K separate out the channels received at their respective ports 116-1, . . . , 116-K. In one embodiment, each splitter 118-1, . . . , 118-K provides N outputs, e.g., 4 outputs or other appropriate number of outputs. Each of the N outputs is coupled through a corresponding receiver/demodulator pair to an input of a corresponding MAC circuit. For example, as shown in Figure 1, splitter 118-1 provides N outputs to receivers 120-1-1, . . . , 120-1-N for downconversion to an intermediate frequency, e.g., a 4 MHz IF signal. In one embodiment, receivers 120-1-1, . . . , 120-1-N are digital receivers that are adapted to receive upstream modulated data signals that have been digitized on the CMTS card from the fiber optic connection from an optical distribution node (See Figure 4). Digital receivers are easily incorporated in circuit 100 and, in one embodiment, all of the digital receivers are incorporated in a single application specific integrated circuit (ASIC). Further, receivers 120-1-1, . . . , 120-1-N are coupled to demodulators 122-1-1, . . . , 122-1-N, respectively. Demodulators 122-1-1, . . . , 122-1-N are coupled to MAC circuits 106-1, . . . , 106-N, respectively. Each of the other receiver/demodulator pairs is connected as shown. In Figure 1, the receivers are designated as 120-X-Y and the demodulators are designated as 122-X-Y. In each case, the X in the reference numeral identifies the associated upstream port for the receiver or demodulator and the Y represents the associated MAC circuit. Thus,

each MAC circuit processes one downstream channel and K upstream channels. Circuit 100 processes N downstream channels and K*N upstream channels.

In Figure 3, graph 300 illustrates an example of an upstream frequency spectrum for one optical node (see Figure 4) serviced by circuit 100. In this example, upstream channels from a selected optical node are located in the 5-42 MHz frequency range. Each channel for the optical node, e.g., channels 302-1, . . . , 302-K, has a separate and distinct frequency band with one band per port of circuit 100. The frequency allocation for the upstream channels of the other optical nodes serviced by circuit 100 are laid out to allow each node to provide a non-interfering upstream channel to each port of circuit 100. Further, in one embodiment, the frequency bands for the various channels of upstream ports 116-1, . . . , 116-K are not contiguous. Further, it is understood that in other embodiments, the upstream channels are located in other appropriate frequency bands, e.g., 5-65 MHz.

FIG. 4
FIG. 5
FIG. 6
FIG. 7
FIG. 8
FIG. 9
FIG. 10
FIG. 11
FIG. 12
FIG. 13
FIG. 14
FIG. 15
FIG. 16
FIG. 17
FIG. 18
FIG. 19
FIG. 20
FIG. 21
FIG. 22
FIG. 23
FIG. 24
FIG. 25
FIG. 26
FIG. 27
FIG. 28
FIG. 29
FIG. 30
FIG. 31
FIG. 32
FIG. 33
FIG. 34
FIG. 35
FIG. 36
FIG. 37
FIG. 38
FIG. 39
FIG. 40
FIG. 41
FIG. 42
FIG. 43
FIG. 44
FIG. 45
FIG. 46
FIG. 47
FIG. 48
FIG. 49
FIG. 50
FIG. 51
FIG. 52
FIG. 53
FIG. 54
FIG. 55
FIG. 56
FIG. 57
FIG. 58
FIG. 59
FIG. 60
FIG. 61
FIG. 62
FIG. 63
FIG. 64
FIG. 65
FIG. 66
FIG. 67
FIG. 68
FIG. 69
FIG. 70
FIG. 71
FIG. 72
FIG. 73
FIG. 74
FIG. 75
FIG. 76
FIG. 77
FIG. 78
FIG. 79
FIG. 80
FIG. 81
FIG. 82
FIG. 83
FIG. 84
FIG. 85
FIG. 86
FIG. 87
FIG. 88
FIG. 89
FIG. 90
FIG. 91
FIG. 92
FIG. 93
FIG. 94
FIG. 95
FIG. 96
FIG. 97
FIG. 98
FIG. 99
FIG. 100
FIG. 101
FIG. 102
FIG. 103
FIG. 104
FIG. 105
FIG. 106
FIG. 107
FIG. 108
FIG. 109
FIG. 110
FIG. 111
FIG. 112
FIG. 113
FIG. 114
FIG. 115
FIG. 116
FIG. 117
FIG. 118
FIG. 119
FIG. 120
FIG. 121
FIG. 122
FIG. 123
FIG. 124
FIG. 125
FIG. 126
FIG. 127
FIG. 128
FIG. 129
FIG. 130
FIG. 131
FIG. 132
FIG. 133
FIG. 134
FIG. 135
FIG. 136
FIG. 137
FIG. 138
FIG. 139
FIG. 140
FIG. 141
FIG. 142
FIG. 143
FIG. 144
FIG. 145
FIG. 146
FIG. 147
FIG. 148
FIG. 149
FIG. 150
FIG. 151
FIG. 152
FIG. 153
FIG. 154
FIG. 155
FIG. 156
FIG. 157
FIG. 158
FIG. 159
FIG. 160
FIG. 161
FIG. 162
FIG. 163
FIG. 164
FIG. 165
FIG. 166
FIG. 167
FIG. 168
FIG. 169
FIG. 170
FIG. 171
FIG. 172
FIG. 173
FIG. 174
FIG. 175
FIG. 176
FIG. 177
FIG. 178
FIG. 179
FIG. 180
FIG. 181
FIG. 182
FIG. 183
FIG. 184
FIG. 185
FIG. 186
FIG. 187
FIG. 188
FIG. 189
FIG. 190
FIG. 191
FIG. 192
FIG. 193
FIG. 194
FIG. 195
FIG. 196
FIG. 197
FIG. 198
FIG. 199
FIG. 200
FIG. 201
FIG. 202
FIG. 203
FIG. 204
FIG. 205
FIG. 206
FIG. 207
FIG. 208
FIG. 209
FIG. 210
FIG. 211
FIG. 212
FIG. 213
FIG. 214
FIG. 215
FIG. 216
FIG. 217
FIG. 218
FIG. 219
FIG. 220
FIG. 221
FIG. 222
FIG. 223
FIG. 224
FIG. 225
FIG. 226
FIG. 227
FIG. 228
FIG. 229
FIG. 230
FIG. 231
FIG. 232
FIG. 233
FIG. 234
FIG. 235
FIG. 236
FIG. 237
FIG. 238
FIG. 239
FIG. 240
FIG. 241
FIG. 242
FIG. 243
FIG. 244
FIG. 245
FIG. 246
FIG. 247
FIG. 248
FIG. 249
FIG. 250
FIG. 251
FIG. 252
FIG. 253
FIG. 254
FIG. 255
FIG. 256
FIG. 257
FIG. 258
FIG. 259
FIG. 260
FIG. 261
FIG. 262
FIG. 263
FIG. 264
FIG. 265
FIG. 266
FIG. 267
FIG. 268
FIG. 269
FIG. 270
FIG. 271
FIG. 272
FIG. 273
FIG. 274
FIG. 275
FIG. 276
FIG. 277
FIG. 278
FIG. 279
FIG. 280
FIG. 281
FIG. 282
FIG. 283
FIG. 284
FIG. 285
FIG. 286
FIG. 287
FIG. 288
FIG. 289
FIG. 290
FIG. 291
FIG. 292
FIG. 293
FIG. 294
FIG. 295
FIG. 296
FIG. 297
FIG. 298
FIG. 299
FIG. 300
FIG. 301
FIG. 302
FIG. 303
FIG. 304
FIG. 305
FIG. 306
FIG. 307
FIG. 308
FIG. 309
FIG. 310
FIG. 311
FIG. 312
FIG. 313
FIG. 314
FIG. 315
FIG. 316
FIG. 317
FIG. 318
FIG. 319
FIG. 320
FIG. 321
FIG. 322
FIG. 323
FIG. 324
FIG. 325
FIG. 326
FIG. 327
FIG. 328
FIG. 329
FIG. 330
FIG. 331
FIG. 332
FIG. 333
FIG. 334
FIG. 335
FIG. 336
FIG. 337
FIG. 338
FIG. 339
FIG. 340
FIG. 341
FIG. 342
FIG. 343
FIG. 344
FIG. 345
FIG. 346
FIG. 347
FIG. 348
FIG. 349
FIG. 350
FIG. 351
FIG. 352
FIG. 353
FIG. 354
FIG. 355
FIG. 356
FIG. 357
FIG. 358
FIG. 359
FIG. 360
FIG. 361
FIG. 362
FIG. 363
FIG. 364
FIG. 365
FIG. 366
FIG. 367
FIG. 368
FIG. 369
FIG. 370
FIG. 371
FIG. 372
FIG. 373
FIG. 374
FIG. 375
FIG. 376
FIG. 377
FIG. 378
FIG. 379
FIG. 380
FIG. 381
FIG. 382
FIG. 383
FIG. 384
FIG. 385
FIG. 386
FIG. 387
FIG. 388
FIG. 389
FIG. 390
FIG. 391
FIG. 392
FIG. 393
FIG. 394
FIG. 395
FIG. 396
FIG. 397
FIG. 398
FIG. 399
FIG. 400
FIG. 401
FIG. 402
FIG. 403
FIG. 404
FIG. 405
FIG. 406
FIG. 407
FIG. 408
FIG. 409
FIG. 410
FIG. 411
FIG. 412
FIG. 413
FIG. 414
FIG. 415
FIG. 416
FIG. 417
FIG. 418
FIG. 419
FIG. 420
FIG. 421
FIG. 422
FIG. 423
FIG. 424
FIG. 425
FIG. 426
FIG. 427
FIG. 428
FIG. 429
FIG. 430
FIG. 431
FIG. 432
FIG. 433
FIG. 434
FIG. 435
FIG. 436
FIG. 437
FIG. 438
FIG. 439
FIG. 440
FIG. 441
FIG. 442
FIG. 443
FIG. 444
FIG. 445
FIG. 446
FIG. 447
FIG. 448
FIG. 449
FIG. 450
FIG. 451
FIG. 452
FIG. 453
FIG. 454
FIG. 455
FIG. 456
FIG. 457
FIG. 458
FIG. 459
FIG. 460
FIG. 461
FIG. 462
FIG. 463
FIG. 464
FIG. 465
FIG. 466
FIG. 467
FIG. 468
FIG. 469
FIG. 470
FIG. 471
FIG. 472
FIG. 473
FIG. 474
FIG. 475
FIG. 476
FIG. 477
FIG. 478
FIG. 479
FIG. 480
FIG. 481
FIG. 482
FIG. 483
FIG. 484
FIG. 485
FIG. 486
FIG. 487
FIG. 488
FIG. 489
FIG. 490
FIG. 491
FIG. 492
FIG. 493
FIG. 494
FIG. 495
FIG. 496
FIG. 497
FIG. 498
FIG. 499
FIG. 500
FIG. 501
FIG. 502
FIG. 503
FIG. 504
FIG. 505
FIG. 506
FIG. 507
FIG. 508
FIG. 509
FIG. 510
FIG. 511
FIG. 512
FIG. 513
FIG. 514
FIG. 515
FIG. 516
FIG. 517
FIG. 518
FIG. 519
FIG. 520
FIG. 521
FIG. 522
FIG. 523
FIG. 524
FIG. 525
FIG. 526
FIG. 527
FIG. 528
FIG. 529
FIG. 530
FIG. 531
FIG. 532
FIG. 533
FIG. 534
FIG. 535
FIG. 536
FIG. 537
FIG. 538
FIG. 539
FIG. 540
FIG. 541
FIG. 542
FIG. 543
FIG. 544
FIG. 545
FIG. 546
FIG. 547
FIG. 548
FIG. 549
FIG. 550
FIG. 551
FIG. 552
FIG. 553
FIG. 554
FIG. 555
FIG. 556
FIG. 557
FIG. 558
FIG. 559
FIG. 560
FIG. 561
FIG. 562
FIG. 563
FIG. 564
FIG. 565
FIG. 566
FIG. 567
FIG. 568
FIG. 569
FIG. 570
FIG. 571
FIG. 572
FIG. 573
FIG. 574
FIG. 575
FIG. 576
FIG. 577
FIG. 578
FIG. 579
FIG. 580
FIG. 581
FIG. 582
FIG. 583
FIG. 584
FIG. 585
FIG. 586
FIG. 587
FIG. 588
FIG. 589
FIG. 590
FIG. 591
FIG. 592
FIG. 593
FIG. 594
FIG. 595
FIG. 596
FIG. 597
FIG. 598
FIG. 599
FIG. 600
FIG. 601
FIG. 602
FIG. 603
FIG. 604
FIG. 605
FIG. 606
FIG. 607
FIG. 608
FIG. 609
FIG. 610
FIG. 611
FIG. 612
FIG. 613
FIG. 614
FIG. 615
FIG. 616
FIG. 617
FIG. 618
FIG. 619
FIG. 620
FIG. 621
FIG. 622
FIG. 623
FIG. 624
FIG. 625
FIG. 626
FIG. 627
FIG. 628
FIG. 629
FIG. 630
FIG. 631
FIG. 632
FIG. 633
FIG. 634
FIG. 635
FIG. 636
FIG. 637
FIG. 638
FIG. 639
FIG. 640
FIG. 641
FIG. 642
FIG. 643
FIG. 644
FIG. 645
FIG. 646
FIG. 647
FIG. 648
FIG. 649
FIG. 650
FIG. 651
FIG. 652
FIG. 653
FIG. 654
FIG. 655
FIG. 656
FIG. 657
FIG. 658
FIG. 659
FIG. 660
FIG. 661
FIG. 662
FIG. 663
FIG. 664
FIG. 665
FIG. 666
FIG. 667
FIG. 668
FIG. 669
FIG. 670
FIG. 671
FIG. 672
FIG. 673
FIG. 674
FIG. 675
FIG. 676
FIG. 677
FIG. 678
FIG. 679
FIG. 680
FIG. 681
FIG. 682
FIG. 683
FIG. 684
FIG. 685
FIG. 686
FIG. 687
FIG. 688
FIG. 689
FIG. 690
FIG. 691
FIG. 692
FIG. 693
FIG. 694
FIG. 695
FIG. 696
FIG. 697
FIG. 698
FIG. 699
FIG. 700
FIG. 701
FIG. 702
FIG. 703
FIG. 704
FIG. 705
FIG. 706
FIG. 707
FIG. 708
FIG. 709
FIG. 710
FIG. 711
FIG. 712
FIG. 713
FIG. 714
FIG. 715
FIG. 716
FIG. 717
FIG. 718
FIG. 719
FIG. 720
FIG. 721
FIG. 722
FIG. 723
FIG. 724
FIG. 725
FIG. 726
FIG. 727
FIG. 728
FIG. 729
FIG. 730
FIG. 731
FIG. 732
FIG. 733
FIG. 734
FIG. 735
FIG. 736
FIG. 737
FIG. 738
FIG. 739
FIG. 740
FIG. 741
FIG. 742
FIG. 743
FIG. 744
FIG. 745
FIG. 746
FIG. 747
FIG. 748
FIG. 749
FIG. 750
FIG. 751
FIG. 752
FIG. 753
FIG. 754
FIG. 755
FIG. 756
FIG. 757
FIG. 758
FIG. 759
FIG. 760
FIG. 761
FIG. 762
FIG. 763
FIG. 764
FIG. 765
FIG. 766
FIG. 767
FIG. 768
FIG. 769
FIG. 770
FIG. 771
FIG. 772
FIG. 773
FIG. 774
FIG. 775
FIG. 776
FIG. 777
FIG. 778
FIG. 779
FIG. 780
FIG. 781
FIG. 782
FIG. 783
FIG. 784
FIG. 785
FIG. 786
FIG. 787
FIG. 788
FIG. 789
FIG. 790
FIG. 791
FIG. 792
FIG. 793
FIG. 794
FIG. 795
FIG. 796
FIG. 797
FIG. 798
FIG. 799
FIG. 800
FIG. 801
FIG. 802
FIG. 803
FIG. 804
FIG. 805
FIG. 806
FIG. 807
FIG. 808
FIG. 809
FIG. 810
FIG. 811
FIG. 812
FIG. 813
FIG. 814
FIG. 815
FIG. 816
FIG. 817
FIG. 818
FIG. 819
FIG. 820
FIG. 821
FIG. 822
FIG. 823
FIG. 824
FIG. 825
FIG. 826
FIG. 827
FIG. 828
FIG. 829
FIG. 830
FIG. 831
FIG. 832
FIG. 833
FIG. 834
FIG. 835
FIG. 836
FIG. 837
FIG. 838
FIG. 839
FIG. 840
FIG. 841
FIG. 842
FIG. 843
FIG. 844
FIG. 845
FIG. 846
FIG. 847
FIG. 848
FIG. 849
FIG. 850
FIG. 851
FIG. 852
FIG. 853
FIG. 854
FIG. 855
FIG. 856
FIG. 857
FIG. 858
FIG. 859
FIG. 860
FIG. 861
FIG. 862
FIG. 863
FIG. 864
FIG. 865
FIG. 866
FIG. 867
FIG. 868
FIG. 869
FIG. 870
FIG. 871
FIG. 872
FIG. 873
FIG. 874
FIG. 875
FIG. 876
FIG. 877
FIG. 878
FIG. 879
FIG. 880
FIG. 881
FIG. 882
FIG. 883
FIG. 884
FIG. 885
FIG. 886
FIG. 887
FIG. 888
FIG. 889
FIG. 890
FIG. 891
FIG. 892
FIG. 893
FIG. 894
FIG. 895
FIG. 896
FIG. 897
FIG. 898
FIG. 899
FIG. 900
FIG. 901
FIG. 902
FIG. 903
FIG. 904
FIG. 905
FIG. 906
FIG. 907
FIG. 908
FIG. 909
FIG. 910
FIG. 911
FIG. 912
FIG. 913
FIG. 914
FIG. 915
FIG. 916
FIG. 917
FIG. 918
FIG. 919
FIG. 920
FIG. 921
FIG. 922
FIG. 923
FIG. 924
FIG. 925
FIG. 926
FIG. 927
FIG. 928
FIG. 929
FIG. 930
FIG. 931
FIG. 932
FIG. 933
FIG. 934
FIG. 935
FIG. 936
FIG. 937
FIG. 938
FIG. 939
FIG. 940
FIG. 941
FIG. 942
FIG. 943
FIG. 944
FIG. 945
FIG. 946
FIG. 947
FIG. 948
FIG. 949
FIG. 950
FIG. 951
FIG. 952
FIG. 953
FIG. 954
FIG. 955
FIG. 956
FIG. 957
FIG. 958
FIG. 959
FIG. 960
FIG. 961
FIG. 962
FIG. 963
FIG. 964
FIG. 965
FIG. 966
FIG. 967
FIG. 968
FIG. 969
FIG. 970
FIG. 971
FIG. 972
FIG. 973
FIG. 974
FIG. 975
FIG. 976
FIG. 977
FIG. 978
FIG. 979
FIG. 980
FIG. 981
FIG. 982
FIG. 983
FIG. 984
FIG. 985
FIG. 986
FIG. 987
FIG. 988
FIG. 989
FIG. 990
FIG. 991
FIG. 992
FIG. 993
FIG. 994
FIG. 995
FIG. 996
FIG. 997
FIG. 998
FIG. 999
FIG. 1000

FIG. 4 is a block diagram of one embodiment of a system, indicated generally at 400, including a multi-channel cable modem termination system 404 that supports multiple downstream channels according to the teachings of the present invention. System 400 includes head end 402. Among other components, head end 402 includes a multi-channel CMTS 404 that supports multiple downstream channels and multiple upstream channels on a single card or chassis. Advantageously, CMTS 404 has a physical configuration that uses the same number of upstream and downstream ports as in existing cards and chassis, but provides more downstream and upstream channels than existing cards and chassis. Thus, CMTS 404 allows a larger number of subscribers to be supported than existing CMTS cards and chassis. In one embodiment, CMTS 404 is constructed as described above with respect to Figures 1A, 1B, 2, and/or 3.

Head end 402 is coupled to a plurality of optical distribution nodes 406-1, . . . , 406-N. Each optical distribution node represents a separate MAC domain for CMTS 404. Head end 402 is coupled to optical distribution nodes 406-1, . . . , 406-N over downstream optical fibers 414. Each of optical distribution nodes 406-1, . . . , 406-N is further coupled to a distribution network of coaxial cables represented by coaxial cable 416. Each of optical distribution nodes 406-1, . . . , 406-N includes

circuitry that is adapted to convert optical signals from head end 402 into electrical signals for transmission over coaxial cable. Further, optical distribution nodes 406-1, . . . , 406-N each include circuitry that is further adapted to convert electrical signals from coaxial cables to optical signals for transmission to head end 402.

5 Coaxial cable 416 provides connection for terminal equipment to network 400. For example, taps, represented by tap 418, provide a connection mechanism for terminal equipment, such as cable modem 408. In one embodiment, cable modem 408 comprises a cable modem according to the data over cable service interface specification (DOCSIS) standard

10 Head end 402 provides a downstream path for data from CMTS 404. The downstream data path includes electrical to optical converter (E/O) 410 coupled in series with splitter 412 between the downstream port (DS) of CMTS 404 and optical fibers 414. In this manner, the downstream data signals from CMTS 404 are provided over optical fibers 414 to optical distribution nodes 406-1, . . . , 406-N for
15 distribution to selected terminal equipment.

 Head end 402 also includes an upstream path for data from terminal equipment. In the upstream, optical distribution nodes 406-1, . . . , 406-N are coupled to optical to electrical converters (O/E) 422-1, . . . , 422-N, respectively, over upstream optical fibers 420. Each of the upstream optical fibers 420 carries a
20 plurality of upstream channels and is coupled to one of upstream ports, US1, . . . , USK, of CMTS 404.

Conclusion

 Embodiments of the present invention have been described. In these embodiments, a cable modem termination system (CMTS) is provided that provides
25 an increase in the number of subscribers supported by a single CMTS card or chassis while using the same physical interface to the system. In one embodiment, this is accomplished by using a plurality of media access control (MAC) circuits. Each MAC circuit supports a single downstream channel. The downstream channels are combined and upconverted using a single upconverter. Advantageously, the reuse of
30 the upconverter allows sufficient savings in space on the CMTS card or chassis that multiple downstream channels can be supported.

